

# Package ‘arcgislayers’

September 19, 2025

**Type** Package

**Title** Harness ArcGIS Data Services

**Version** 0.5.0

**Description** Enables users of 'ArcGIS Enterprise', 'ArcGIS Online', or 'ArcGIS Platform' to read, write, publish, or manage vector and raster data via ArcGIS location services REST API endpoints  
<<https://developers.arcgis.com/rest/>>.

**License** Apache License (>= 2)

**URL** <https://developers.arcgis.com/r-bridge>,  
<https://github.com/R-ArcGIS/arcgislayers>

**BugReports** <https://github.com/R-ArcGIS/arcgislayers/issues>

**Depends** R (>= 4.2.0)

**Imports** arcgisutils (>= 0.4.0), arcpbf (>= 0.1.5), cli, httr2 (>= 1.0.5), jsonify, lifecycle, RcppSimdJson (>= 0.1.13), rlang, sf, terra, utils

**Suggests** testthat (>= 3.0.0), vctrs, curl, dplyr

**Config/testthat/edition** 3

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**NeedsCompilation** no

**Author** Josiah Parry [aut, cre] (ORCID:  
<<https://orcid.org/0000-0001-9910-865X>>),  
Eli Pousson [ctb] (ORCID: <<https://orcid.org/0000-0001-8280-1706>>),  
Kenneth Vernon [ctb] (ORCID: <<https://orcid.org/0000-0003-0098-5092>>),  
Martha Bass [ctb] (ORCID: <<https://orcid.org/0009-0004-0268-5426>>),  
Antony Barja [ctb] (ORCID: <<https://orcid.org/0000-0001-5921-2858>>)

**Maintainer** Josiah Parry <josiah.parry@gmail.com>

**Repository** CRAN

**Date/Publication** 2025-09-19 05:10:27 UTC

Contents

|                                   |           |
|-----------------------------------|-----------|
| add_features . . . . .            | 2         |
| add_item . . . . .                | 4         |
| add_layer_definition . . . . .    | 7         |
| arc_open . . . . .                | 8         |
| arc_raster . . . . .              | 10        |
| arc_read . . . . .                | 12        |
| arc_select . . . . .              | 14        |
| clear_query . . . . .             | 16        |
| create_feature_server . . . . .   | 17        |
| encode_field_values . . . . .     | 19        |
| get_layer . . . . .               | 20        |
| get_layer_estimates . . . . .     | 21        |
| list_raster_fns . . . . .         | 22        |
| prepare_spatial_filter . . . . .  | 23        |
| query_layer_attachments . . . . . | 24        |
| set_layer_aliases . . . . .       | 26        |
| truncate_layer . . . . .          | 27        |
| update_attachments . . . . .      | 28        |
| update_params . . . . .           | 30        |
| <b>Index</b>                      | <b>32</b> |

---

|              |                                      |
|--------------|--------------------------------------|
| add_features | <i>Add Features to Feature Layer</i> |
|--------------|--------------------------------------|

---

Description

Delete features from a feature layer based on object ID, a where clause, or a spatial filter.

Usage

```
add_features(  
  x,  
  .data,  
  chunk_size = 500,  
  match_on = c("name", "alias"),  
  rollback_on_failure = TRUE,  
  progress = TRUE,  
  token = arc_token()  
)  
  
delete_features(  
  x,  
  object_ids = NULL,  
  where = NULL,  
  filter_geom = NULL,
```

```

    predicate = "intersects",
    rollback_on_failure = TRUE,
    chunk_size = 500,
    progress = TRUE,
    token = arc_token()
  )

update_features(
  x,
  .data,
  chunk_size = 500,
  match_on = c("name", "alias"),
  rollback_on_failure = TRUE,
  progress = TRUE,
  token = arc_token()
)

```

## Arguments

|                     |   |
|---------------------|---|
| x                   | an object of class FeatureLayer   |
| .data               | an object of class sf or data.frame   |
| chunk_size          | the maximum number of features to add at a time   |
| match_on            | whether to match on the alias or the field name. Default, the alias. See Details for more.  |
| rollback_on_failure | default TRUE. Specifies whether the edits should be applied only if all submitted edits succeed.  |
| progress            | default TRUE. A progress bar to be rendered by httr2 to track requests.   |
| token               | default arc_token(). An httr2_token.  |
| object_ids          | a numeric vector of object IDs to be deleted.   |
| where               | a simple SQL where statement indicating which features should be deleted. When the where statement evaluates to TRUE, those values will be deleted.             |
| filter_geom         | an object of class bbox, sfc or sfg used to filter query results based on a predicate function.   |
| predicate           | Spatial predicate to use with filter_geom. Default "intersects". Possible options are "intersects", "contains", "crosses", "overlaps", "touches", and "within". |

## Details

### [Experimental]

For a more detailed guide to adding, updating, and deleting features, view the tutorial on the [R-ArcGIS Bridge website](#).

Regarding the match\_on argument: when publishing an object to an ArcGIS Portal from R, the object's names are provided as the alias. The object's names are subject to change according to the

standards of the ArcGIS REST API. For example, "Sepal.Length" is changed to "Sepal.Width" in the name field but the alias remains "Sepal.Length". For that reason, we match on the alias name by default. Change this argument to match based on the field name.

### Value

- `add_features()` returns a `data.frame` with columns `objectId`, `uniqueId`, `globalId`, `success`
- `update_features()` returns a list with an element named `updateResults` which is a `data.frame` with columns `objectId`, `uniqueId`, `globalId`, `success`
- `delete_features()` returns a list with an element named `deleteResults` which is a `data.frame` with columns `objectId`, `uniqueId`, `globalId`, `success`

### Examples

```
## Not run:
# this is pseudo-code and will not work
fplayer <- arc_open(furl)

# add sf objects to existing feature service
add_features(fplayer, sfobj)

# delete all features
delete_features(fplayer, where = "1 = 1")

# update features
update_features(fplayer, dfobj)

## End(Not run)
```

---

add\_item

*Publish Content*

---

### Description

Publishes an `sf` or `data.frame` object to an ArcGIS Portal as a `FeatureCollection`.

### Usage

```
add_item(
  x,
  title,
  description = "",
  tags = character(0),
  snippet = "",
  categories = character(0),
  async = FALSE,
  type = "Feature Service",
  token = arc_token()
```

```

)

publish_item(
  item_id,
  publish_params = .publish_params(),
  file_type = "featureCollection",
  token = arc_token()
)

publish_layer(
  x,
  title,
  ...,
  publish_params = .publish_params(title, target_crs = sf::st_crs(x)),
  token = arc_token()
)

.publish_params(
  name = NULL,
  description = NULL,
  copyright = NULL,
  target_crs = 3857,
  max_record_count = 2000L
)

```

## Arguments

|                             |  |
|-----------------------------|--|
| <code>x</code>              | an object of class <code>data.frame</code> . This can be an <code>sf</code> object or <code>tibble</code> or any other subclass of <code>data.frame</code> . |
| <code>title</code>          | A user-friendly string title for the layer that can be used in a table of contents.  |
| <code>description</code>    | a length 1 character vector containing the description of the item that is being added. Note that the value cannot be larger than 64kb.                      |
| <code>tags</code>           | a character vector of tags to add to the item.   |
| <code>snippet</code>        | a length 1 character vector with no more than 2048 characters.   |
| <code>categories</code>     | a character vector of the categories of the item.  |
| <code>async</code>          | default <code>FALSE</code> . Cannot be changed at this time.   |
| <code>type</code>           | default <code>"Feature Service"</code> . Must not be changed at this time.   |
| <code>token</code>          | an <code>httr2_token</code> as created by <code>auth_code()</code> or similar  |
| <code>item_id</code>        | the ID of the item to be published.  |
| <code>publish_params</code> | a list of named values of the <code>publishParameters</code> . Must match the values in the <a href="#">/publish endpoint documentation</a> .                |
| <code>file_type</code>      | default <code>"featureCollection"</code> . Cannot be changed.  |
| <code>...</code>            | arguments passed into <code>add_item()</code> .  |
| <code>name</code>           | a scalar character of the name of the layer. Must be unique.   |

|                  |   |
|------------------|---|
| copyright        | an optional character scalar containing copyright text to add to the published Feature Service. |
| target_crs       | the CRS of the Feature Service to be created. By default, EPSG:3857.                            |
| max_record_count | the maximum number of records that can be returned from the created Feature Service.            |

## Details

### [Experimental]

- `add_item()` takes a `data.frame` like object and uploads it as an item in your portal.
- `publish_item()` takes an ID of an item in your portal and publishes it as a feature service.
- `publish_layer()` is a high-level wrapper that first adds an object as an item in your portal and subsequently publishes it for you.
- `.publish_params()` is a utility function to specify optional publish parameters such as copyright text, and the spatial reference of the published feature collection.

Note that there is *only* support for feature services meaning that only tables and feature layers can be made by these functions.

#### **Publish Parameters:**

When publishing an item to a portal, a number of **publish parameters** can be provided. Most importantly is the `targetSR` which will be the CRS of the hosted feature service. By default this is EPSG:3857.

`publish_layer()` will use the CRS of the input object, `x`, by default. If publishing content in two steps with `add_item()` and `publish_item()`, use `.publish_params()` to craft your publish parameters. Ensure that the CRS provided to `target_crs` matches that of the item you added with `add_item()`.

## Value

A named list containing the url of the newly published service.

## Examples

```
## Not run:
nc <- sf::st_read(system.file("shape/nc.shp", package = "sf"))
x <- nc[1:5, 13]

token <- auth_code()
set_arc_token(token)

publish_res <- publish_layer(
  x, "North Carolina SIDS sample"
)

## End(Not run)
```

---

add\_layer\_definition    *Add, update, or delete a Feature Layer definition*

---

## Description

Each layer of a feature service is defined by a "definition." The definition describes the service such as its fields, symbology, indexes and more.

## Usage

```
add_layer_definition(x, ..., async = FALSE, token = arc_token())
```

```
update_layer_definition(x, ..., async = FALSE, token = arc_token())
```

```
delete_layer_definition(x, ..., async = FALSE, token = arc_token())
```

## Arguments

|       |  |
|-------|--|
| x     | A Feature Layer, Table, or Feature Service class object.                                   |
| ...   | Additional parameters for the "addToDefinition" or "updateDefinition" body of the request. |
| async | Default FALSE. If TRUE, support asynchronous processing for the request.                   |
| token | an http2_token as created by auth_code() or similar  |

## Details

### [Experimental]

- Use [add\\_layer\\_definition\(\)](#) for adding fields to a feature service or otherwise adding to the definition of a feature layer.
- Use [update\\_layer\\_definition\(\)](#) to modify existing aspects of the definition properties.
- Use [delete\\_layer\\_definition\(\)](#) to delete properties from the layer definition.

Examples of properties include the layer name, renderer, or field properties. Named parameters passed to ... must have names matching supported definitions. Parameters are converted to a JSON addToDefinition, updateDefinition, or deleteFromDefinition query parameter using [jsonify::to\\_json\(\)](#).

See the ArcGIS REST API documentation on Administer Hosted Feature Services for more details:

- see the [layerDefinition](#) object documentation.
- adding definitions for a [FeatureLayer](#) or a [FeatureService](#)
- updating definitions for a [FeatureLayer](#) or a [FeatureService](#)
- deleting definitions for a [FeatureLayer](#) or a [FeatureService](#)

**Value**

If `async = FALSE`, return an updated "FeatureServer" or "FeatureLayer" object with the added, updated, or deleted definitions. If `async = TRUE`, the input Feature Layer or Feature Server object `x` is returned as is.

**Examples**

```
## Not run:
if (interactive()) {
  # authenticate
  set_arc_token(auth_code())

  # publish a layer
  published <- publish_layer(penguins, "Penguin Test")

  penguin_fl <- arc_open(published$services$encodedServiceURL) |>
    get_layer(0)

  # Update the name of the layer
  update_layer_definition(
    penguin_fl,
    name = "New Layer Name"
  )

  # add an index on the the layer
  add_layer_definition(
    penguin_fl,
    indexes = list(
      name = "index1",
      fields = "species",
      isUnique = FALSE,
      isAscending = FALSE,
      description = "Example index"
    )
  )

  # refresh the layer to get the updates
  penguin_fl <- refresh_layer(penguin_fl)
  penguin_fl[["indexes"]]
}

## End(Not run)
```

---

arc\_open

---

*Access a Data Service or Portal Item*


---

**Description**

Access a resource on ArcGIS Online, Enterprise, or Location Platform.



**Usage**

```
arc_open(url, host = arc_host(), token = arc_token())
```

**Arguments**

|       |  |
|-------|--|
| url   | a url to a service such as a feature service, image server, or map server. Alternatively, an item ID of a portal item or portal url. |
| host  | default "https://www.arcgis.com". The host of your ArcGIS Portal.  |
| token | an http2_token as created by <code>auth_code()</code> or similar   |

**Details**

- To read the underlying attribute data from a `FeatureLayer`, `Table`, or `ImageServer` use `arc_select()`.
- If you have a `MapServer` or `FeatureServer` access the individual layers using `get_layer()`. For
- Use `arc_raster()` to get imagery as a terra raster object.

**[Stable]**

**Value**

Depending on item ID or URL returns a `PortalItem`, `FeatureLayer`, `Table`, `FeatureServer`, `ImageServer`, or `MapServer`, `GeocodeServer`, among other. Each of these objects is a named list containing the properties of the service.

**See Also**

`arc_select` `arc_raster` `get_layer`

**Examples**

```
## Not run:

# FeatureServer ID
arc_open("3b7221d4e47740cab9235b839fa55cd7")

# FeatureLayer
furl <- paste0(
  "https://services3.arcgis.com/ZvidGQkLaDJxRSJ2/arcgis/rest/services/",
  "PLACES_LocalData_for_BetterHealth/FeatureServer/0"
)

arc_open(furl)

# Table
furl <- paste0(
  "https://services.arcgis.com/P3ePLMys2RVChkJx/arcgis/rest/services/",
  "USA_Wetlands/FeatureServer/1"
)
```

```

arc_open(furl)

# ImageServer
arc_open(
  "https://landsat2.arcgis.com/arcgis/rest/services/Landsat/MS/ImageServer"
)

# FeatureServer
furl <- paste0(
  "https://services3.arcgis.com/ZvidGQkLaDJxRSJ2/arcgis/rest/services/",
  "PLACES_LocalData_for_BetterHealth/FeatureServer"
)

arc_open(furl)

# MapServer
map_url <- paste0(
  "https://services.arcgisonline.com/ArcGIS/rest/services/",
  "World_Imagery/MapServer"
)

arc_open(map_url)

## End(Not run)

```

---

arc\_raster

*Read from an Image Server*


---

## Description

Given an ImageServer export an image as a terra SpatRaster object. See [terra::rast](#).

## Usage

```

arc_raster(
  x,
  xmin,
  xmax,
  ymin,
  ymax,
  bbox_crs = NULL,
  crs = sf::st_crs(x),
  width = NULL,
  height = NULL,
  format = "tiff",
  ...,
  raster_fn = NULL,
  token = arc_token()
)

```

**Arguments**

|           |   |
|-----------|---|
| x         | an ImageServer as created with <code>arc_open()</code> .  |
| xmin      | the minimum bounding longitude value.   |
| xmax      | the maximum bounding longitude value.   |
| ymin      | that minimum bounding latitude value.   |
| ymax      | the maximum bounding latitude value.  |
| bbox_crs  | the CRS of the values passed to xmin, xmax, ymin, and ymax. If not specified, uses the CRS of x.                                      |
| crs       | the CRS of the resultant raster image and the provided bounding box defined by xmin, xmax, ymin, ymax (passed outSR query parameter). |
| width     | default NULL. Cannot exceed <code>x[["maxImageWidth"]]</code> .   |
| height    | default NULL. Cannot exceed <code>x[["maxImageHeight"]]</code> .  |
| format    | default "tiff". Must be one of "jpgpng", "png", "png8", "png24", "jpg", "bmp", "gif", "tiff", "png32", "bip", "bsq", "lerc".          |
| ...       | additional key value pairs to be passed to <code>httr2::req_body_form()</code> .  |
| raster_fn | a scalar string with the name of the service's raster function. See <code>list_raster_fns()</code> for available raster functions.    |
| token     | default <code>arc_token()</code> authorization token.   |

**Details****[Experimental]****Value**

An object of class `SpatRaster`.

**Examples**

```
## Not run:
img_url <- "https://landsat2.arcgis.com/arcgis/rest/services/Landsat/MS/ImageServer"

landsat <- arc_open(img_url)

arc_raster(
  landsat,
  xmin = -71,
  xmax = -67,
  ymin = 43,
  ymax = 47.5,
  bbox_crs = 4326,
  width = 100,
  height = 100
)

## End(Not run)
```

arc\_read

*Read an ArcGIS FeatureLayer, Table, or ImageServer***Description**

`arc_read()` combines the functionality of `arc_open()` with `arc_select()` or `arc_raster()` to read an ArcGIS FeatureLayer, Table, or ImageServer to an sf or SpatRaster object. Optionally, set, check, or modify names for the returned data frame or sf object using the `col_names` and `name_repair` parameters. For ease of use and convenience, `arc_read()` allows users to access and query a FeatureLayer, Table, or ImageServer with a single function call instead of combining `arc_open()` and `arc_select()`. The conventions of `col_select` are based on functions for reading tabular data in the `{readr}` package.

**Usage**

```
arc_read(
  url,
  col_names = TRUE,
  col_select = NULL,
  n_max = Inf,
  name_repair = "unique",
  crs = NULL,
  ...,
  fields = NULL,
  alias = "drop",
  token = arc_token()
)
```

**Arguments**

|                          |  |
|--------------------------|--|
| <code>url</code>         | a url to a service such as a feature service, image server, or map server. Alternatively, an item ID of a portal item or portal url.   |
| <code>col_names</code>   | Default TRUE. Column names or name handling rule. <code>col_names</code> can be TRUE, FALSE, NULL, or a character vector: <ul style="list-style-type: none"> <li>• If TRUE, use existing default column names for the layer or table. If FALSE or NULL, column names will be generated automatically: X1, X2, X3 etc.</li> <li>• If <code>col_names</code> is a character vector, values replace the existing column names. <code>col_names</code> can't be length 0 or longer than the number of fields in the returned layer.</li> </ul> |
| <code>col_select</code>  | Default NULL. A character vector of the field names to be returned. By default, all fields are returned.   |
| <code>n_max</code>       | Defaults to Inf or an option set with <code>options("arccgislayers.n_max" = &lt;max records&gt;)</code> . Maximum number of records to return.   |
| <code>name_repair</code> | Default "unique". See <code>vctrs::vec_as_names()</code> for details. If <code>name_repair</code> = NULL and <code>alias</code> = "replace" may include invalid names.   |

|        |   |
|--------|---|
| crs    | the spatial reference to be returned. If the CRS is different than the CRS for the input FeatureLayer, a transformation will occur server-side. Ignored if x is a Table.  |
| ...    | Additional arguments passed to <code>arc_select()</code> if URL is a FeatureLayer or Table or <code>arc_raster()</code> if URL is an ImageLayer.  |
| fields | Default NULL. a character vector of the field names to returned. By default all fields are returned. Ignored if col_names is supplied.  |
| alias  | Use of field alias values. Default <code>c("drop", "label", "replace")</code> . There are three options: <ul style="list-style-type: none"> <li>• "drop": field alias values are ignored.</li> <li>• "label": field alias values are assigned as a label attribute for each field.</li> <li>• "replace": field alias values replace existing column names. col_names</li> </ul> |
| token  | an http2_token as created by <code>auth_code()</code> or similar  |

## Details

### [Experimental]

## Value

An sf object, a data.frame, or an object of class SpatRaster.

## See Also

`arc_select()`; `arc_raster()`

## Examples

```
## Not run:
furl <- "https://sampleserver6.arcgisonline.com/arcgis/rest/services/Census/MapServer/3"

# read entire service
arc_read(furl)

# apply tolower() to column names
arc_read(url, name_repair = tolower)

# use paste0 to prevent CRAN check NOTE
furl <- paste0(
  "https://sampleserver6.arcgisonline.com/arcgis/rest/services/",
  "EmergencyFacilities/FeatureServer/0"
)

# use field aliases as column names
arc_read(furl, alias = "replace")

# read an ImageServer directly
img_url <- "https://landsat2.arcgis.com/arcgis/rest/services/Landsat/MS/ImageServer"
```

```

arc_read(
  img_url,
  width = 100, height = 100,
  xmin = -71, ymin = 43,
  xmax = -67, ymax = 47.5,
  bbox_crs = 4326
)

## End(Not run)

```

---

arc\_select

*Query a Feature Service*


---

## Description

`arc_select()` takes a `FeatureLayer`, `Table`, or `ImageServer` object and returns data from the layer as an `sf` object or `data.frame` respectively.

## Usage

```

arc_select(
  x,
  ...,
  fields = NULL,
  where = NULL,
  crs = sf::st_crs(x),
  geometry = TRUE,
  filter_geom = NULL,
  predicate = "intersects",
  n_max = Inf,
  page_size = NULL,
  token = arc_token()
)

```

## Arguments

|                       |   |
|-----------------------|---|
| <code>x</code>        | an object of class <code>FeatureLayer</code> , <code>Table</code> , or <code>ImageServer</code> .   |
| <code>...</code>      | additional query parameters passed to the API.  |
| <code>fields</code>   | a character vector of the field names that you wish to be returned. By default all fields are returned.   |
| <code>where</code>    | a simple SQL where statement indicating which features should be selected.  |
| <code>crs</code>      | the spatial reference to be returned. If the CRS is different than the CRS for the input <code>FeatureLayer</code> , a transformation will occur server-side. Ignored if <code>x</code> is a <code>Table</code> . |
| <code>geometry</code> | default <code>TRUE</code> . If geometries should be returned. Ignored for <code>Table</code> objects.   |

|             |   |
|-------------|---|
| filter_geom | an object of class bbox, sfc or sfg used to filter query results based on a predicate function.   |
| predicate   | Spatial predicate to use with filter_geom. Default "intersects". Possible options are "intersects", "contains", "crosses", "overlaps", "touches", and "within". |
| n_max       | the maximum number of features to return. By default returns every feature available. Unused at the moment.   |
| page_size   | the maximum number of features to return per request. Useful when requests return a 500 error code. See Details.  |
| token       | an http2_token as created by auth_code() or similar   |

## Details

See [reference documentation](#) for possible arguments.

FeatureLayers can contain very dense geometries with a lot of coordinates. In those cases, the feature service may time out before all geometries can be returned. To address this issue, we can reduce the number of features returned per each request by reducing the value of the page\_size parameter.

arc\_select() works by sending a single request that counts the number of features that will be returned by the current query. That number is then used to calculate how many "pages" of responses are needed to fetch all the results. The number of features returned (page size) is set to the maxRecordCount property of the layer by default. However, by setting page\_size to be smaller than the maxRecordCount we can return fewer geometries per page and avoid time outs.

## [Experimental]

## Value

An sf object, or a data.frame

## Examples

```
## Not run:
# define the feature layer url
furl <- paste0(
  "https://services3.arcgis.com/ZvidGQkLaDJxRSJ2/arcgis/rest",
  "/services/PLACES_LocalData_for_BetterHealth/FeatureServer/0"
)

flayer <- arc_open(furl)

arc_select(
  flayer,
  fields = c("StateAbbr", "TotalPopulation")
)

arc_select(
  flayer,
  fields = c("OBJECTID", "PlaceName"),
```

```

    where = "TotalPopulation > 1000000"
)

## End(Not run)

```

---

clear\_query

*Utility functions*


---

## Description

Utility functions

## Usage

```

clear_query(x)

list_fields(x)

pull_field_aliases(x)

list_items(x)

refresh_layer(x)

```

## Arguments

x                      an object of class FeatureLayer, Table, or ImageServer.

## Details

### [Experimental]

- `list_fields()` returns a data.frame of the fields in a FeatureLayer or Table
- `list_items()` returns a data.frame containing the layers or tables in a FeatureServer or MapServer
- `clear_query()` removes any saved query in a FeatureLayer or Table object
- `refresh_layer()` syncs a FeatureLayer or Table with the remote resource picking up any changes that may have been made upstream. Returns an object of class x.
- `pull_field_aliases()` returns a named list of the field aliases from a FeatureLayer or Table

## Value

See Details.



## Examples

```
## Not run:
furl <- paste0(
  "https://services3.arcgis.com/ZvidGQkLaDJxRSJ2/arcgis/rest/services/",
  "PLACES_LocalData_for_BetterHealth/FeatureServer/0"
)

fplayer <- arc_open(furl)

# list fields available in a layer
list_fields(fplayer)

# remove any queries stored in the query attribute
clear_query(update_params(fplayer, outFields = "*"))

# refresh metadata of an object
refresh_layer(fplayer)

map_url <- paste0(
  "https://services.arcgisonline.com/ArcGIS/rest/services/",
  "World_Imagery/MapServer"
)

# list all items in a server object
list_items(arc_open(map_url))

## End(Not run)
```

---

create\_feature\_server *Create a FeatureServer*

---

## Description

Creates an empty FeatureServer with no additional layers.

## Usage

```
create_feature_server(
  service_name,
  description = "",
  crs = 3857,
  capabilities = c("create", "delete", "query", "update", "editing"),
  query_formats = c("json", "geojson"),
  initial_extent = list(xmin = NULL, xmax = NULL, ymin = NULL, ymax = NULL),
  max_record_count = 1000L,
  allow_updates = TRUE,
  copyright = "",
  has_static_data = FALSE,
  xss_prevention = xss_defaults(),
```

```

    token = arc_token()
)

xss_defaults()

```

### Arguments

|                  |  |
|------------------|--|
| service_name     | Feature Service name.  |
| description      | default blank. The description of the feature server.  |
| crs              | default 3857. A coordinate reference system to set for the feature server. Must be compatible with <code>sf::st_crs()</code> . |
| capabilities     | default full capabilities. Character vector of capabilities.   |
| query_formats    | default json and geojson. May be restricted by site-wide settings.   |
| initial_extent   | optional. A named list with element of xmin, xmax, ymin, and ymax. Values must be in the same CRS as crs.                      |
| max_record_count | default 1000. The maximum number of records that can be retrieved from a layer in one request.                                 |
| allow_updates    | default TRUE. Determine if geometries can be updated.  |
| copyright        | default blank. Copyright notice to provide in the Feature Server   |
| has_static_data  | default FALSE. Indicates if data is changing.  |
| xss_prevention   | cross-site-scripting prevention is enabled by default. See details for more.   |
| token            | an <code>httr2_token</code> as created by <code>auth_code()</code> or similar  |

### Details

#### [Experimental]

### Value

If a `FeatureServer` is created successfully, a `FeatureServer` object is returned based on the newly created feature server's url.

### Examples

```

## Not run:
  set_arc_token(auth_code())
  create_feature_server("My empty feature server")

## End(Not run)

```

---

|                     |                             |
|---------------------|-----------------------------|
| encode_field_values | <i>Encode Domain Values</i> |
|---------------------|-----------------------------|

---

## Description

`encode_field_values()` can replace column values based on codedValue type field domains from a corresponding Table or FeatureLayer object created with `arc_open()`.

## Usage

```
encode_field_values(
  .data,
  .layer,
  field = NULL,
  codes = c("replace", "label"),
  call = rlang::caller_env()
)
```

## Arguments

|                     |  |
|---------------------|--|
| <code>.data</code>  | A data frame returned by <code>arc_select()</code> or <code>arc_read()</code> .  |
| <code>.layer</code> | A Table or FeatureLayer object. Required.  |
| <code>field</code>  | Optional character vector with names of fields to replace. Fields that do not have coded value domains are ignored. Defaults to NULL to replace or label all fields with coded value domains.  |
| <code>codes</code>  | Use of field alias values. Defaults to "replace". There are two options: <ul style="list-style-type: none"> <li>"replace": coded values replace existing column values.</li> <li>"label": coded values are applied as value labels via a "label" attribute.</li> </ul> |
| <code>call</code>   | The execution environment of a currently running function, e.g. <code>caller_env()</code> . The function will be mentioned in error messages as the source of the error. See the <code>call</code> argument of <code>abort()</code> for more information.              |

## Value

A data.frame with fields encoded with their respective domains.

## Examples

```
layer <- arc_open(
  "https://geodata.baltimorecity.gov/egis/rest/services/Housing/dmxOwnership/MapServer/0"
)

res <- arc_select(
  layer,
  n_max = 100,
  where = "RESPAGCY <> ' '",
```

```

    fields = "RESPAGCY"
  )
  encoded <- encode_field_values(res, layer)
  table(encoded$RESPAGCY)

```

---

get\_layer

---

*Extract a layer from a Feature or Map Server*


---

## Description

These helpers provide easy access to the layers contained in a FeatureServer, MapServer, or GroupLayer.

## Usage

```

get_layer(x, id = NULL, name = NULL, token = arc_token())

get_all_layers(x, token = arc_token())

get_layers(x, id = NULL, name = NULL, token = arc_token())

```

## Arguments

|       |   |
|-------|---|
| x     | an object of class FeatureServer, MapServer, or GroupLayer.   |
| id    | default NULL. A numeric vector of unique ID of the layer you want to retrieve. This is a scalar in get_layer().                             |
| name  | default NULL. The name associated with the layer you want to retrieve. name is mutually exclusive with id. This is a scalar in get_layer(). |
| token | an http2_token as created by auth_code() or similar   |

## Details

### [Experimental]

The id and name arguments must match the field values of the respective names as seen in the output of list\_items()

## Value

- get\_layer() returns a single FeatureLayer or Table based on its ID
- get\_layers() returns a list of the items specified by the id or name argument
- get\_all\_layers() returns a named list with an element layers and tables. Each a list containing FeatureLayer and Tables respectively.

## Examples

```
## Not run:
# FeatureServer
furl <- paste0(
  "https://services3.arcgis.com/ZvidGQkLaDJxRSJ2/arcgis/rest/services/",
  "PLACES_LocalData_for_BetterHealth/FeatureServer"
)

fserv <- arc_open(furl)

fserv
get_layer(fserv, 0)
get_layers(fserv, name = c("Tracts", "ZCTAs"))
get_all_layers(fserv)

## End(Not run)
```

---

|                     |                      |
|---------------------|----------------------|
| get_layer_estimates | <i>Get Estimates</i> |
|---------------------|----------------------|

---

## Description

Get Estimates

## Usage

```
get_layer_estimates(x, token = arc_token())
```

## Arguments

|       |   |
|-------|---|
| x     | an object of class FeatureLayer, Table, or ImageServer. |
| token | an http2_token as created by auth_code() or similar     |

## Value

A named list containing all estimate info. If extent is present, it is available as an object of class bbox.

## References

[ArcGIS REST Doc](#)

**Examples**

```
furl <- paste0(
  "https://services.arcgis.com/P3ePLMys2RVChkJx/ArcGIS/rest/services/",
  "USA_Counties_Generalized_Boundaries/FeatureServer/0"
)

county_fl <- arc_open(furl)
get_layer_estimates(county_fl)
```

---

|                 |  |
|-----------------|--|
| list_raster_fns | <i>List Available Raster Functions</i> |
|-----------------|--|

---

**Description**

This function returns the rasterFunctionInfos field of the ImageServer's metadata as a data.frame. If the field does not exist then an error is emitted.

**Usage**

```
list_raster_fns(x, arg = rlang::caller_arg(x), call = rlang::caller_call())

list_service_raster_fns(
  x,
  arg = rlang::caller_arg(x),
  call = rlang::caller_call()
)
```

**Arguments**

|      |  |
|------|--|
| x    | an ImageServer.  |
| arg  | An argument name in the current function.  |
| call | <p>The execution environment of a currently running function, e.g. call = caller_env(). The corresponding function call is retrieved and mentioned in error messages as the source of the error.</p> <p>You only need to supply call when throwing a condition from a helper function which wouldn't be relevant to mention in the message.</p> <p>Can also be NULL or a <a href="#">defused function call</a> to respectively not display any call or hard-code a code to display.</p> <p>For more information about error calls, see <a href="#">Including function calls in error messages</a>.</p> |

**Value**

a data.frame of the available raster functions.

**Examples**

```
## Not run:
# use paste to avoid cran note
furl <- paste0(
  "https://di-usfsdata.img.arcgis.com/arcgis/rest/services",
  "/FIA_BIGMAP_2018_Tree_Species_Aboveground_Biomass/ImageServer"
)

service <- arc_open(furl)
raster_fns <- list_service_raster_fns(service)
head(raster_fns)

## End(Not run)
```

---

```
prepare_spatial_filter
```

*Prepare JSON for use as a spatial filter based on feature geometry or bounding box input*

---

**Description**

`prepare_spatial_filter()` prepares a named list with ESRI JSON geometry for use as a spatial filter based on a a sfc, sfg, or bbox input object.

`match_spatial_rel()` takes a scalar character vector with a predicate name to a type of ESRI spatial relation.

**Usage**

```
prepare_spatial_filter(
  filter_geom,
  crs,
  predicate,
  error_call = rlang::caller_env()
)

match_spatial_rel(predicate, error_call = rlang::caller_env())
```

**Arguments**

|                          |   |
|--------------------------|---|
| <code>filter_geom</code> | an object of class bbox, sfc or sfg used to filter query results based on a predicate function.   |
| <code>crs</code>         | a representation of a coordinate reference system.  |
| <code>predicate</code>   | Spatial predicate to use with <code>filter_geom</code> . Default "intersects". Possible options are "intersects", "contains", "crosses", "overlaps", "touches", and "within". |
| <code>error_call</code>  | default <code>rlang::caller_env()</code> .  |

**Details**

Using sfc objects as filter\_geom

**[Experimental]**

If an sfc object is provided it will be transformed to the layers spatial reference. If the sfc is missing a CRS (or is an sf object) it is assumed to use the same spatial reference as the FeatureLayer. If the sfc object has multiple features, the features are unioned with `sf::st_union()`. If an sfc object has MULTIPOLYGON geometry, the features are cast to POLYGON geometry and only the first element is used.

**Value**

`prepare_spatial_filter()` returns a named list with the geometryType, geometry (as Esri JSON), and spatial relation predicate.

`match_spatial_rel()` returns one of the following spatial binary predicates:

- `esriSpatialRelIntersects`
- `esriSpatialRelContains`
- `esriSpatialRelCrosses`
- `esriSpatialRelOverlaps`
- `esriSpatialRelTouches`
- `esriSpatialRelWithin`

**Examples**

```
prepare_spatial_filter(sf::st_point(c(0, 5)), 4326, "intersects")
```

---

query\_layer\_attachments

*Query and Download Feature Service Attachments*

---

**Description**

Query attachment information using `query_layer_attachments()` and download attachments using `download_attachments()`.

**Usage**

```
query_layer_attachments(
  x,
  definition_expression = "1=1",
  attachments_definition_expression = NULL,
  object_ids = NULL,
  global_ids = NULL,
  attachment_types = NULL,
  keywords = NULL,
```



```

    return_metadata = TRUE,
    ...,
    token = arc_token()
)

download_attachments(
  attachments,
  out_dir,
  ...,
  overwrite = FALSE,
  .progress = TRUE,
  token = arc_token()
)

```

### Arguments

|  |  |
|--|--|
| <code>x</code>                                 | an object of class <code>FeatureLayer</code> , <code>Table</code> , or <code>ImageServer</code> .  |
| <code>definition_expression</code>             | default 1 = 1. A SQL where clause that is applied to the layer. Only those records that conform to this expression will be returned. This parameter is required if neither <code>object_ids</code> or <code>global_ids</code> have been defined. |
| <code>attachments_definition_expression</code> | default NULL. A SQL where clause that is applied to the attachment metadata. only attachments that conform to this expression will be returned.  |
| <code>object_ids</code>                        | mutually exclusive with <code>definition_expression</code> and <code>global_ids</code> . The object IDs of the features to query attachments of.   |
| <code>global_ids</code>                        | mutually exclusive with <code>definition_expression</code> and <code>object_ids</code> . The global IDs of the features to query attachments of.   |
| <code>attachment_types</code>                  | default NULL. A character vector of attachment types to filter on.   |
| <code>keywords</code>                          | default NULL. A character vector of the keywords to filter on.   |
| <code>return_metadata</code>                   | default TRUE. Returns metadata stored in the <code>exifInfo</code> field.  |
| <code>...</code>                               | unused   |
| <code>token</code>                             | an <code>httr2_token</code> as created by <code>auth_code()</code> or similar  |
| <code>attachments</code>                       | a <code>data.frame</code> created by <code>query_layer_attachments()</code> . Must contain the columns <code>name</code> , <code>url</code> , and <code>contentType</code> .   |
| <code>out_dir</code>                           | the path to the folder to download the file  |
| <code>overwrite</code>                         | default FALSE. A   |
| <code>.progress</code>                         | default TRUE. Whether a progress bar should be provided.   |

### Value

`query_layer_attachments()` returns a `data.frame`.

`download_attachments()` returns a list. If an error occurs, the condition is captured and returned in the list. Otherwise the path to the file that was downloaded is returned.

## References

[ArcGIS REST API Documentation](#)

## Examples

```
## Not run:
# create a url path that isn't too wide for CRAN
furl <- paste(
  c(
    "https://services1.arcgis.com/hLJbHVT9ZrDIzK0I",
    "arcgis/rest/services/v8_Wide_Area_Search_Form_Feature_Layer___a2fe9c",
    "FeatureServer/0"
  ),
  collapse = "/"
)
# connect to the layer
layer <- arc_open(furl)

# get the attachment info
att <- query_layer_attachments(layer)

# download them to a path
download_attachments(att, "layer_attachments")

## End(Not run)
```

---

|                   |  |
|-------------------|--|
| set_layer_aliases | <i>Set column labels or names based FeatureLayer or Table data frame field aliases</i> |
|-------------------|--|

---

## Description

`set_layer_aliases()` can replace or label column names based on the the field aliases from a corresponding Table or FeatureLayer object created with `arc_open()`. Optionally repair names using `vctrs::vec_as_names()`.

## Usage

```
set_layer_aliases(
  .data,
  .layer,
  name_repair = "unique",
  alias = c("replace", "label"),
  call = rlang::caller_env()
)
```

**Arguments**

|                          |  |
|--------------------------|--|
| <code>.data</code>       | A data frame returned by <code>arc_select()</code> or <code>arc_read()</code> .  |
| <code>.layer</code>      | A Table or FeatureLayer object. Required.  |
| <code>name_repair</code> | Default "unique". See <code>vctrs::vec_as_names()</code> for details. If <code>name_repair = NULL</code> and <code>alias = "replace"</code> may include invalid names.   |
| <code>alias</code>       | Use of field alias values. Defaults to "replace". There are two options: <ul style="list-style-type: none"> <li>• "label": field alias values are assigned as a label attribute for each field.</li> <li>• "replace": field alias values replace existing column names.</li> </ul> |
| <code>call</code>        | The execution environment of a currently running function, e.g. <code>caller_env()</code> . The function will be mentioned in error messages as the source of the error. See the <code>call</code> argument of <code>abort()</code> for more information.                          |

**Value**

A data.frame. When `alias = "replace"`, the column names are modified. When `alias = "label"` each column has a new label attribute.

**Examples**

```
furl <- paste0(
  "https://services.arcgis.com/P3ePLMys2RVChkJx/ArcGIS/",
  "rest/services/USA_Counties_Generalized_Boundaries/FeatureServer/0"
)

# open the feature service
flayer <- arc_open(furl)

# select first five rows
five_counties <- arc_select(flayer, n_max = 5)

# add aliases
with_aliases <- set_layer_aliases(five_counties, flayer)

# preview the new names
str(with_aliases, give.attr = FALSE)
```

---

truncate\_layer

*Truncate a Feature Layer*


---

**Description**

Removes all features in a Feature Layer or Table and resets the object ID counter. Truncating a Feature Layer does not change the schema of the data (does not add, remove, or alter existing database columns, constraints, or indexes).

**Usage**

```
truncate_layer(x, async = FALSE, attachment_only = FALSE, token = arc_token())
```

**Arguments**

|                 |  |
|-----------------|--|
| x               | an object of class FeatureLayer, Table, or ImageServer.  |
| async           | default FALSE. It is recommended to set TRUE for larger datasets.  |
| attachment_only | default FALSE. Deletes all the attachments for this layer. None of the layer features will be deleted when TRUE. |
| token           | an http2_token as created by auth_code() or similar  |

**Value**

a named list with the name "success" and a value of TRUE or FALSE

**References**

[ArcGIS Developers Rest API Doc](#)

**Examples**

```
## Not run:

# authorize using code flow
set_arc_token(auth_code())

# create a FeatureLayer object
flayer <- arc_open("your-feature-layer-url")

# truncate it
truncate_layer(flayer)

## End(Not run)
```

---

|                    |   |
|--------------------|---|
| update_attachments | <i>Update Feature Service Attachments</i> |
|--------------------|---|

---

**Description**

Feature Services can contain attachments that are associated with a single feature ID. `update_features()` enables you to update the attachments of multiple features at once by generating multiple update requests and performing them in parallel.

**Usage**

```
update_attachments(
  x,
  feature_id,
  attachment_id,
  path,
  .progress = TRUE,
  token = arc_token()
)
```

**Arguments**

|                            |  |
|----------------------------|--|
| <code>x</code>             | an object of class <code>FeatureLayer</code> , <code>Table</code> , or <code>ImageServer</code> .                            |
| <code>feature_id</code>    | a vector of object IDs that corresponds to the feature of the corresponding <code>attachment_id</code> .                     |
| <code>attachment_id</code> | the ID of the attachment—this corresponds to the <code>id</code> column returned from <code>query_layer_attachments()</code> |
| <code>path</code>          | a vector of the same length as <code>feature_id</code> indicating where the attachment exists.                               |
| <code>.progress</code>     | default <code>TRUE</code> . Whether a progress bar should be provided.   |
| <code>token</code>         | an <code>httr2_token</code> as created by <code>auth_code()</code> or similar  |

**Details**

**[Experimental]** To rename or otherwise modify an attachment in a Feature Service, you must first download that attachment, modify the file on disk, and then upload it again. This is a limitation of ArcGIS Online and Enterprise. If you'd like to see this changed, please submit a community idea at [community.esri.com](https://community.esri.com).

If any requests fail, the requests are added as the `errors` attribute to the resultant `data.frame`.

**Value**

a `data.frame` with 2 columns returning the status of the update.

**References**

See [API documentation](#) for more.

**Examples**

```
## Not run:
if (interactive()) {
  library(arcgisutils)

  # authenticate
  set_arc_token(auth_user())

  # open a feature service
```

```

feature_layer <- arc_open("your-item-id") |>
  # layer ID of the feature service
  get_layer(0)

# query attachment layer information
attachments <- query_layer_attachments(feature_layer)

# create a temporary directory
tmp <- tempdir()

# download attachments to the temporary directory
download_attachments(attachments, tmp)

# get original paths
fps <- file.path(tmp, attachments$name)

# prepend attachments with the date
new_filenames <- paste0(Sys.Date(), "-", basename(attachments$name))

# create new file paths
new_fps <- file.path(dirname(fps), new_filenames)

# rename the files
file.rename(fps, new_fps)

# update the attachments
update_res <- update_attachments(
  feature_layer,
  # OID of the feature <> attachment relationship
  attachments$parentObjectId,
  # the attachment ID
  attachments$id,
  # the path to the attachment on disk
  new_fps
)
}

## End(Not run)

```

---

update\_params

*Modify query parameters*


---

## Description

`update_params()` takes named arguments and updates the query.

## Usage

```
update_params(x, ...)
```

**Arguments**

*x*                      a FeatureLayer or Table object  
...                      key value pairs of query parameters and values.

**Value**

An object of the same class as *x*

**Examples**

```
## Not run:  
furl <- paste0(  
  "https://services.arcgis.com/P3ePLMYs2RVChkJx/ArcGIS/rest/services/",  
  "USA_Major_Cities_/FeatureServer/0"  
)  
  
flayer <- arc_open(furl)  
update_params(flayer, outFields = "NAME")  
  
## End(Not run)
```

# Index

.publish\_params (add\_item), 4

abort(), 19, 27

add\_features, 2

add\_item, 4

add\_layer\_definition, 7

add\_layer\_definition(), 7

arc\_open, 8

arc\_open(), 12

arc\_raster, 10

arc\_raster(), 9, 12, 13

arc\_read, 12

arc\_read(), 12

arc\_select, 14

arc\_select(), 9, 12–14

clear\_query, 16

create\_feature\_server, 17

defused function call, 22

delete\_features (add\_features), 2

delete\_layer\_definition  
(add\_layer\_definition), 7

delete\_layer\_definition(), 7

download\_attachments  
(query\_layer\_attachments), 24

encode\_field\_values, 19

encode\_field\_values(), 19

get\_all\_layers (get\_layer), 20

get\_layer, 20

get\_layer(), 9

get\_layer\_estimates, 21

get\_layers (get\_layer), 20

httr2::req\_body\_form(), 11

Including function calls in error  
messages, 22

jsonify::to\_json(), 7

list\_fields (clear\_query), 16

list\_items (clear\_query), 16

list\_raster\_fns, 22

list\_raster\_fns(), 11

list\_service\_raster\_fns  
(list\_raster\_fns), 22

match\_spatial\_rel  
(prepare\_spatial\_filter), 23

match\_spatial\_rel(), 23, 24

prepare\_spatial\_filter, 23

prepare\_spatial\_filter(), 23, 24

publish\_item (add\_item), 4

publish\_layer (add\_item), 4

pull\_field\_aliases (clear\_query), 16

query\_layer\_attachments, 24

refresh\_layer (clear\_query), 16

set\_layer\_aliases, 26

set\_layer\_aliases(), 26

sf::st\_union(), 24

terra::rast, 10

truncate\_layer, 27

update\_attachments, 28

update\_features (add\_features), 2

update\_layer\_definition  
(add\_layer\_definition), 7

update\_layer\_definition(), 7

update\_params, 30

update\_params(), 30

vctrs::vec\_as\_names(), 12, 26, 27

xss\_defaults (create\_feature\_server), 17